

Amendments to the Claims

The following listing of the claims will replace all prior versions, and listings, of claims in the application. Inserted material is underlined and deleted material is shown in strikethrough to show the changes made.

1. (Currently Amended) A method for networking a plurality of clients in a personal video recording (“PVR”) system, said method comprising the steps of:
 - receiving a plurality of television signals;
 - tuning each of said television signals in one of a plurality of tuners;
 - buffering said television signals on a storage medium in at least one PVR media server;
 - coupling a plurality of clients, over a network, to said PVR media server;
 - receiving at least one request from each of at least two clients for at least one service in said PVR system; and
 - allocating resources of said PVR system to said clients, as appropriate, to deliver said service to said clients;
 - designating one of at least three states to a first tuner, the at least three states comprising at least: a busy state, a maybe free state, and a totally free state,
wherein the designating of the states are used to allocate by the PVR system for
resolving conflicts in allocating tuners to the requesting clients,
 - the resources of the PVR system comprising the tuners,
 - the first tuner comprising a first designated state.

2. (Original) The method as set forth in claim 1, wherein:
 - the step of receiving at least one request comprises the step of receiving a request to record a television program; and
 - the step of allocating resources of said PVR system to said clients comprises the steps of:
 - assigning a tuner to record said television program;
 - allocating space on said storage medium to record said television program; and
 - storing said television signal on said storage medium during a time scheduled for said television program.
3. (Previously Presented) The method as set forth in claim 1, wherein:
 - the step of receiving at least one request comprises the step of receiving a request to watch buffered live television; and
 - the step of allocating resources of said PVR system comprises the steps of:
 - assigning a tuner to said client;
 - generating a buffer position to identify a location within said television signal for playback of said television signal at a client; and
 - transferring said television signal to said client, so as to deliver said television signal using said buffer position.
4. (Original) The method as set forth in claim 1, wherein:
 - the step of receiving at least one request comprises the step of receiving a request to receive television signals from a specific television service provider; and

the step of allocating resources of said PVR system comprises the steps of:
identifying one or more tuners coupled to receive television signals from said television service provider; and
assigning a tuner from said tuners to receive television signals from said television service provider.

5. (Original) The method as set forth in claim 1, wherein the step of allocating resources of said PVR system to said clients comprises the step of resolving any conflicts of assigning resources to said clients.

6. (Original) The method as set forth in claim 5, wherein:
the step of receiving at least one request comprises the step of receiving a request to watch buffered live television at a channel selected; and
the step of resolving any conflicts of assigning resources comprises the steps of:
determining whether one of said tuners is available to receive said television signal;
if so, assigning said tuner to receive said television signal at said channel selected;
if not, determining which tuners are potentially available;
querying clients assigned to said tuners potentially available to determine whether said clients desire to change a current channel of said tuner to said channel selected; and
assigning a tuner potentially available to receive a television signal at said channel selected if no clients cancel a change of said current channel.

7. (Original) The method as set forth in claim 5, wherein:

the step of receiving at least one request comprises the step of receiving a request to record a television program; and

the step of resolving any conflicts of assigning resources comprises the steps of:

determining whether one of said tuners is available to receive said television signal;

if so, assigning said tuner to receive said television signal;

if not, determining which tuners are potentially available;

querying clients assigned to said tuners potentially available to determine whether said clients desire to cancel recordation of said television program; and

assigning a tuner potentially available to receive said television signal if no clients cancel recordation of said television program.

8. (Previously Presented) The method as set forth in claim 5, further comprising the steps of:

designating a totally free tuner state to a tuner not assigned to a client;

designating a maybe free tuner state to a tuner assigned to a client but not currently executing a scheduled recordation; and

designating a busy tuner state to a tuner currently executing a scheduled recordation.

9. (Currently Amended) A personal video recording (“PVR”) media server comprising:

an input for receiving a plurality of television signals;

a plurality of tuners for tuning each of said television signals;

a storage medium for buffering said television signals;

a network interface for coupling a plurality of clients, over a network, to said PVR media server; and

said PVR media server for receiving at least one request from each of at least two clients for at least one service in a PVR system, and for allocating resources of said PVR system to said clients, as appropriate, to deliver said service to said clients;

the PVR server configured to designate one of at least three states to a first tuner, the at least three states comprising at least: a busy state, a maybe free state, and a totally free state,

wherein the designating of the states are used to allocate for resolving conflicts in
allocating tuners to the requesting clients,

the resources of the PVR system comprising the tuners,

the first tuner comprising a first designated state.

10. (Original) The PVR media server as set forth in claim 9, wherein:

said input further for receiving a request to record a television program; and

said PVR media server further for assigning a tuner to record said television program, for allocating space on said storage medium to record said television program, and for storing said television signal on said storage medium during a time scheduled for said television program.

11. (Original) The PVR media server as set forth in claim 9, wherein:

said input further for receiving a request to watch buffered live television; and

said PVR media server further for assigning a tuner to watch said buffered live television, for generating a buffer position to identify a location within said television signal for playback of

said television signal at a client, and for transferring said television to said client, so as to deliver said television signal using said buffer position.

12. (Original) The PVR media server as set forth in claim 9, wherein:
said input further for receiving at least one request comprises the step of receiving a request to receive television signals from a specific television service provider; and
said PVR media server further for identifying one or more tuners coupled to receive television signals from said television service provider, and for assigning a tuner from said tuners identified to said client.

13. (Original) The PVR media server as set forth in claim 9, said PVR media server further for resolving any conflicts of assigning resources to said clients.

14. (Original) The PVR media server as set forth in claim 13, wherein:
said input further for receiving a request to watch buffered live television at a channel selected; and
said PVR media server further for determining whether one of said tuners is available to receive said television signal;
if so, for assigning said tuner to receive said television signal at said channel selected;
if not, for determining which tuners are potentially available, for querying clients assigned to said tuners potentially available to determine whether said clients desire to change a current channel of said tuner to said channel selected, and for assigning a tuner potentially

available to receive a television signal at said channel selected if no clients cancel a change of said current channel.

15. (Original) The PVR media server as set forth in claim 13, wherein:
said input further for receiving a request to record a television program; and
said PVR media server further for determining whether one of said tuners is available to receive said television signal;
if so, for assigning said tuner to receive said television signal;
if not, for determining which tuners are potentially available, for querying clients assigned to said tuners potentially available to determine whether said clients desire to cancel recordation of said television program, and for assigning a tuner potentially available to receive said television signal if no clients cancel recordation of said television program.

16. (Previously Presented) The PVR media server as set forth in claim 13, said PVR media server further
for designating a totally free tuner state to a tuner not assigned to a client,
for designating a maybe free tuner state to a tuner assigned to a client but not currently executing a scheduled recordation, and
for designating a busy tuner state to a tuner currently executing a scheduled recordation.

17. (Currently Amended) A personal video recording (“PVR”) system comprising: at least one PVR media server comprising:

an input for receiving a plurality of television signals;
a plurality of tuners for tuning each of said television signals;
a storage medium for buffering said television signals;
a network; and
a plurality of clients, coupled over said network to said PVR media server, for receiving at least one request from each of at least two clients for at least one service in said PVR system, and for allocating resources of said PVR system to said clients, as appropriate, to deliver said service to said clients;

the PVR system configured to designate assign one of at least three states to a first tuner, the at least three states comprising at least: a busy state, a maybe free state, and a totally free state,

wherein the designating of the states are is used to allocate for resolving conflicts in allocating tuners to the requesting clients,

the resources of the PVR system comprising the tuners,
the first tuner comprising a first designated state.

18. (Previously Presented) The system of claim 17, further configured for resolving conflicts of assigning resources to the clients,

the busy state for indicating that the server is currently receiving a program by using the first tuner;

the maybe free state for indicating a probability that a client is viewing a program by using the first tuner, wherein when a tuner is designated as in the maybe free state a user selects

to view a program at a client and the PVR system is missing information as to whether the user is still viewing the program; and

the totally free state for indicating when a tuner is not allocated by a scheduler and a client is not viewing programming by using the tuner; wherein:

the input is further for receiving one or more of:

a request to watch buffered live television at a channel selected, and

a request to record a television program;

the PVR media server is further for determining whether one of the tuners is available to receive the television signal;

if so, for assigning a first tuner to receive the television signal at the channel selected;

if not, for determining which tuners are potentially available, for querying clients assigned to the tuners potentially available to determine whether the clients desire to change a current channel of the tuner to the channel selected, and for assigning a tuner potentially available to receive a television signal at the channel selected if no clients cancel a change of the current channel and if no clients cancel recordation of the television program.

19. (Previously Presented) The system of claim 17, further comprising a new device coupled to the network, and a set of compatible devices on the network include one or more PVR-media servers configured for storing pre-recorded video and for providing live television, wherein to discover services on the network, the new device transmits a discovery command and waits for a response,

wherein a first PVR-media server on the network exposes an interface to allow the new device to aggregate programming provided by the PVR-media server in response to the request, the new device connects to a compatible device via a supporting protocol, and the compatible device translates the protocol for the appropriate device using state information.

20. (Previously Presented) The system of claim 19, wherein the new device comprises a television, and the compatible device supports an industry standard protocol, wherein the industry standard protocol is selected to communicate to the compatible device and to use the services provided by the compatible device.

21. (Previously Presented) The system of claim 17, wherein the PVR system is further configured for discovering devices in the networked PVR system, wherein when a new device not currently connected to the network is connected to the network, in order to communicate on the network, the new device obtains a network address,

the system further comprising a home media network, and a plurality of devices having network addresses, wherein if the underlying network supports TCP/IP, then the new device determines if there is an available DHCP server;

if so, the DHCP server assigns the network address to the new device;

if a DHCP server is not available to assign the new device a network address, then the new device selects a network address from a pool and determines whether any other device on the network has the selected network address, wherein if no other device on the network has the

selected network address, then the new device uses the selected network address, wherein the network addressing allows communication on the network within a single subnet; wherein the new device transmits an announcement command over the network, the format of the announcement command complies with a supported protocol, wherein the new device broadcasts or multicasts the announcement command over the network, the multicast of the announcement command is for expanding subnets if the network includes a gateway, wherein a multicast format is used to specify specific network addresses transmitting an announcement only to those devices on the network interested or compatible with the new device, wherein compatible devices are those devices that are interested in communicating with the new device, wherein a compatible device on the network exposes one or more services to the new device; wherein in response to the new device's announcement command, the new device constructs state information that provides details regarding devices available on the network, the state information comprising protocols and services supported by the networked devices, such that when compatible devices on the network receive the announcement command, the compatible devices add information encapsulated in the announcement command, to a local cache.